

Maxol Unigear 85W/140

Description:

Maxol Unigear 85W/140 is a universal gear oil based on high quality solvent refined base oils and special EP-additives.

- Excellent activity against high temperature load
- Excellent activity against wear, corrosion and foam
- Very special EP-properties
- Excellent "Limited Slip" properties
- Widely usable

Application:

This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable. This product also contains excellent "Limited Slip" properties.

Performance Level:

API GL-4/GL-5/MT-1
Mil-L-2105A/B/C/D/E, Mil-L-PRF-2105E
MAN 341 Typ Z2/E2, MAN 342 Typ M2
Scania STO 1:0
ZF TE-ML 05C/07A/08/12C/16E

Typical Characteristics:

Density at 15 °C, kg/l	0.905
Viscosity 40 °C, mm ² /s	345.80
Viscosity 100 °C, mm ² /s	26.10
Viscosity Index	99
Flash Point COC, °C	222
Pour Point, °C	-18

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

