

Maxol Autotrans

Description:

A very high graded automatic transmission fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

Application:

This This fluid may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required.

Performance Level:

Allison C4
Cat TO-2
DTFR 13C140
Ford Mercon / M2C138-CJ / 166-H
GM Dexron IID
MAN 339 Typ Z1 / V1
MB 236.6 / 236.7
Voith 55.6335 (G607)
ZF TE-ML 09 / 11A / 14A

Typical Characteristics:

Density at 15°C, kg/l	0,859
Viscosity 40 °C, mm ² /s	36,50
Viscosity 100 °C, mm ² /s	7,50
Viscosity Index	162
Flash Point COC, °C	225
Pour Point, °C	-48

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

