

## Maxol Torc 4 TO-4 50

### Description:

A special oil for hydraulic- and transmission equipment formulated with solvent refined base oils and selected additives to obtain the following properties:

- a low pour point
- a very good stability against oxidation
- very good anti
- wear properties, that gives a longer duration of the final drive
- specific friction-properties, which grants an optimum use of the power shift transmissions
- applicable in systems with "wet" brakes
- excellent corrosion and foaming preventive properties

### Performance Level:

|                      |
|----------------------|
| Allison C4           |
| Cat TO-4/TO-2        |
| Komatsu KES 07.868.1 |

### Application:

This oil is special developed for the lubrication of power shift transmissions, differentials, final drives and hydraulic equipment of earth-moving equipment, for which a Caterpillar TO-4 or Allison C4 fluid is required. ***This oil cannot be used in engines.***

### Typical Characteristics:

|                                      |        |
|--------------------------------------|--------|
| Density at 15 °C, kg/l               | 0,899  |
| Viscosity 40 °C, mm <sup>2</sup> /s  | 199,50 |
| Viscosity 100 °C, mm <sup>2</sup> /s | 17,50  |
| Viscosity Index                      | 94     |
| Flash Point COC, °C                  | 240    |
| Pour Point, °C                       | -12    |
| Sulphate Ash, %                      | 1,32   |

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

