

Maxol Semi-Synthetic 10W/40

Description:

Maxol Semi-Synthetic 10W/40 is a universal oil for cars and vans. It can be used in petrol and diesel engines, with or without turbo-charging.

- Lower fuel consumption
- Fast cold start
- Very good detergency and dispersion power
- Very strong protection against wear, corrosion and foaming

Application:

This universal motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Performance Level:

ACEA A3/B4
API SL/CF
MB 229.1
VW 502.00/505.00

Typical Characteristics:

Density at 15 °C, kg/l	0.869
Viscosity -25 °C, mPa.s	6170
Viscosity 40 °C, mm ² /s	90.00
Viscosity 100 °C, mm ² /s	13.50
Viscosity Index	152
Flash Point COC, °C	224
Pour Point, °C	-42
Total Base Number, mgKOH/g	10.2
Sulphate Ash, %	1.29

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

