

## Maxol Specialsynth P 0W30

### Description:

A synthetic, fuel economy, universal motor oil, developed according to the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- a lower fuel consumption
- suitable for modern catalysts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Performance Level:

ACEA C2
API SP
PSA B71 2312
PSA B71 2302

### Application:

This universal, synthetic, fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

### Typical Characteristics:

Density at 15 °C, kg/l	0,849
Viscosity -35 °C, kg/l	6030
Viscosity 40 °C, mm <sup>2</sup> /s	51,80
Viscosity 100 °C, mm <sup>2</sup> /s	9,90
Viscosity Index	180
Flash Point COC, °C	220
Pour Point, °C	-48
Total Base Number, mgKOH/g	11,2
Sulphate Ash, %	0,75

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

