

## Maxol Syntec 5W/40

### Description:

A very modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures -
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Performance Level:

ACEA A3/B4
API SN/CF
MB 229.3 / 226.5
Renault RN0700 / RN0710
VW 502.00 / 505.00
BMW Longlife-01
Fiat 9.55535-M2
GM LL-B-025
Porsche A40
PSA B71 2296

### Application:

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

### Typical Characteristics:

Density at 15°C, kg/l	0,856
Viscosity -30 °C, mPa.s	5880
Viscosity 40 °C, mm <sup>2</sup> /s	92,20
Viscosity 100 °C, mm <sup>2</sup> /s	14,70
Viscosity Index	167
Flash Point COC, °C	228
Pour Point, °C	-42
Total Base Number, mgKOH/g	10,8
Sulphate Ash, %	1,32

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

