

## Maxol Uni Gear LD 75W90

### Description:

This gear oil is a universal full-synthetic gear oil based on high quality synthetic base oils and special EP-additives to obtain the following properties:

- an excellent activity against high temperature load
- a very strong activity against wear, corrosion and foam
- a low pour point
- very special extreme pressure properties
- widely usable

### Performance Level:

API GL-3 / GL-4 / GL-5 / MT-1
MIL-L-2105D / MIL-PRF-2105E, SAE J2360
MAN 341 Typ Z2 / 342 Typ S1
DTFR 12B140 (235.8)
Scania STO 1:1 G / 2:0 A FS
ZF TE-ML 02B / 05A / 12L / 12N
ZF TE-ML 16F / 17B / 19C / 21A
Arvin Meritor 076-N
DAF, Iveco
Mack GO-J
MAN 3343 Typ S / 341 Typ E3 / 341 Typ GA1
MB 235.8 / 235.9
Scania STO 1:0
Volvo 97312
ZF TE-ML 07A / 12B / 16B

### Application:

Ma This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is a universal product widely usable.

### Typical Characteristics:

Density at 15°C, kg/l	0,871
Viscosity 100 °C, mm <sup>2</sup> /s	101,00
Viscosity 40°C, mm <sup>2</sup> /s	15,40
Viscosity Index	161
Flash Point COC, °C	202
Pour Point, °C	-48
Total Base Number, mgKOH/g	2,1

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.