

Maxol Hydraulic Transmission Fluid

Description:

A modern universal hydraulic and transmission oil formulated with solvent refined base oils and selected additives.

- High and stable viscosity index
- Very low pour point
- Very good stability against oxidation
- Good extreme pressure- and anti-wear properties
- Optimal friction properties and therefore applicable in systems with "wet" brakes
- Excellent corrosion and foam preventing properties

Application:

This universal tractor transmission oil (UTTO) has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment.

Performance Level:

API GL-4
Ford M2C134-D, CNH MAT 3525
John Deere J20C
Massey Ferguson M1141/M1143
Cat TO-2
IH Plus (suitable for use)
Case MS1206/MS1207 (suitable for use)
Case MAT 3505/MS 1209 (suitable for use)

Typical Characteristics:

Density at 15 °C, kg/l	0.865
Viscosity 40 °C, mm ² /s	52.00
Viscosity 100 °C, mm ² /s	9.05
Viscosity Index	156
Flash Point COC, °C	244
Pour Point, °C	-36
Total Base Number, mgKOH/g	7.3
Sulphate Ash, %	1.19

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

