Maxol Lubricants

Technical Data

Maxol Tractor Trans Plus

Description:

A very high quality universal hydraulic and transmission oil formulated with high quality base oils and selected additives to obtain the following properties:

- *a high and stable viscosity index*
- *a very low pour point*
- *a very good stability against oxidation*
- *a high thermal stability*
- *good extreme pressure- and anti-wear properties*
- *optimal friction properties and therefor applicable in systems with "wet" brakes*
- *excellent corrosion and foam preventing properties*

Performance Level:

API GL-4
Allison C4
Cat TO-2
Case MS 1210
CNH MAT 3540 / 3525
FNHA-2-C-200.00 / 201.00
Ford M2C86-C / M2C134-D
John Deere J20C/D
Massey Ferguson M1141 / M1143 / M1145
Valtra G2-08 / G2-B10
Volvo WB 101 (97303)
ZF TE-ML 03E / 05F / 06K / 17E / 21F

Application:

This very high-quality universal tractor transmission oil (UTTO) has been developed for heavy loaded hydraulics and transmissions, with or without wet brakes, of agricultural and road-construction equipment. This oil can also be used in certain continuously variable transmissions (CVT) of agricultural and road-construction equipment.

Typical Characteristics:

Density at 15°C, kg/l	*0,870*
Viscosity 40 °C, mm²/s	*66,70*
Viscosity 100 °C, mm²/s	*10,00*
Viscosity Index	*165*
Flash Point COC, °C	*232*
Pour Point, °C	*-42*

Important:
Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol LUBRICANTS YOU CAN TRUST

Maxol Lubricants Ltd.
Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie