

Maxol Extend 15W40

Description:

Maxol Extend is a product of the LB (Level Back-up) product range. These products are based on the officially approved formulas, using the same high-quality additives, but the base oils have been replaced with equivalent alternatives. This creates equivalent products in terms of quality, with a performance level corresponding to the originally approved products.

However, because no field tests have been conducted, the product may be claimed only to meet the mentioned performance levels.

Performance Level:

| |
|-------------------------|
| ACEA E7 |
| API CI-4 / SL |
| Cat ECF-1-a / ECF-2 |
| Cummins CES 20077/20078 |
| Detroit Diesel 93K215 |
| Deutz DQC III-18 |
| DTRF 15B110 |
| Global DHD-1 |
| JASO DH-1 |
| Mack EO-N/EO-M Plus |
| MAN M 3275-1 |
| MB 228.3 |
| MTU Type 2 |
| Renault VI RLD-2 |
| Volvo VDS-3 |

Application:

This engine lubricant is applicable to gasoline and diesel engines (normally- or turboaspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.

Typical Characteristics:

| | |
|--------------------------------------|--------|
| Density at 15°C, kg/l | 0,874 |
| Viscosity -20 °C, mPa.s | 5060 |
| Viscosity 40 °C, mm ² /s | 106,00 |
| Viscosity 100 °C, mm ² /s | 14,60 |
| Viscosity Index | 142 |
| Flash Point COC, °C | 228 |
| Pour Point, °C | -36 |
| Total Base Number, mgKOH/g | 11,1 |
| Sulphate Ash, % | 1,43 |

Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

