

## Maxol Petrol 15/40

### Description:

We've used the latest lubricant technology, combining carefully selected base oils with advanced additives to create this universal Petrol Engine Oil. With Maxol Petrol 15W/40 you'll get much better all-round engine protection, plus a range of added benefits to keep your engine in tiptop condition.

- Perfect lubrication of all motor parts
- Active detergency, preventing from deposits in the combustion zone and at the scavenger ports
- Preventing spark plugs from fouling, in this way securing an optimal output of the engine
- Very effective activity against wear and corrosion
- Very limited formation of smoke
- Self-mixing

### Application:

This engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This special quality of engine oil is mainly developed to allow extended oil drain intervals

and to prevent "bore polishing" (=cylinder wear) in diesel engines. Also, this product is suitable for use in Euro 4 and Euro 5 engines.

### Performance Level:

ACEA A3/B4
A.P.I. SL/CI
MB 228.3/229.1

### Typical Characteristics:

Density at 15 °C, kg/l	0.875
Viscosity -20°C, mPa.s	4590
Viscosity 40 °C, mm <sup>2</sup> /s	99.00
Viscosity 100 °C, mm <sup>2</sup> /s	13.90
Viscosity Index	142
Flash Point COC, °C	212
Pour Point, °C	-36
Total Base Number, mgKOH/g	10.7
Sulphate Ash, %	1.37

### Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)





# TechnicalData

and to prevent "bore polishing" (=cylinder-wear) in diesel engines. Also is this product suitable for application in Euro 4 and Euro 5

**Important:**

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

