

Maxol Slideway 68

Description:

Maxol Slideway 68 is a universal machine tool lubricant, based on mineral oil, under addition of several additives.

- Good resistance against high pressures and high loads
- Very strong adhesion to slides
- Superior "stick-slip" properties
- Very good anti-wear, anti-rust and anti-corrosion properties
- Excellent demulsification properties
- Good filterability

Application:

This oil is a machine tool lubricant specially designed for tableway lubrication, with emphasis on superior stick-slip properties. This machine tool lubricant also meets the requirements of hydraulic systems, gear boxes and spindles in most machine tools.

Performance Level:

DIN 51524/51517
FZG 12
US Steel 224

Typical Characteristics:

Density at 15 °C, kg/l	0.877
Viscosity 40 °C, mm ² /s	68.00
Viscosity 100 °C, mm ² /s	8.60
Viscosity Index	97
Flash Point COC, °C	225
Pour Point, °C	-25
Acid Number, mgKOH/g	0.50

Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

