Maxol Lubricants

Technical Data

Maxol Torc 4 TO-4 50

Description:

A special oil for hydraulic- and transmission equipment formulated with solvent refined base oils and selected additives to obtain the following properties:
- a low pour point
- a very good stability against oxidation
- very good anti
-wear properties, that gives a longer duration of the final drive
- specific friction-properties, which grants an optimum use of the power shift transmissions
- applicable in systems with "wet" brakes
- excellent corrosion and foaming preventive properties

Performance Level:

API GL-4
Allison C4
Cat TO-4 / TO-2
Komatsu KES 07.868.1
Eaton (Vickers) M-2950-S / I-286-S

Application:

This oil is special developed for the lubrication of power shift transmissions, differentials, final drives and hydraulic equipment of earth-moving equipment, for which a Caterpillar TO-4 or Allison C4 fluid is required. ***This oil cannot be used in engines.***

Typical Characteristics:

Density at 15 °C, kg/l	0,898
Viscosity 40 °C, mm²/s	169,00
Viscosity 100 °C, mm²/s	18,10
Viscosity Index	101
Flash Point COC, °C	272
Pour Point, °C	-12
Sulphate Ash, %	0,91

Important:
Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.
Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

Maxol LUBRICANTS YOU CAN TRUST