MAXOL Lubricants

TechnicalData

Maxol Slideway 220

Description:

Maxol Slideway 220 is based upon high-quality, low-aromatic solvent-refined base oils under addition of special additives.

- Very high grade of tackiness, preventing the oil from fling of the chain
- Excellent lubricity

Application:

This chain oil has been specially formulated to lubricate the chain of chain-saws preventing this oil from overheating and loss of strength. The high grade of tackiness prevents the oil to fling from the chain. The chain-saw oil cannot be used for the lubrication of the engine of the saw.

Performance Level:

AGMA 9005-E02
DIN 51517-3 CLP
DIN 51524-2 HLP
ISO 19378 GA & GB
FZG 12

Typical Characteristics:

Density at 15 °C, kg/l	0.898
Viscosity 40 °C, mm²/s	220
Viscosity 100 °C, mm²/s	18.20
Viscosity Index	95
Flash Point COC, °C	245
Pour Point, °C	-15

Important:
Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.
Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

MAXOL Lubricants you can Trust