

Maxol Bio Universal Tractor Transmission Oil

Description:

Maxol Bio Universal Tractor Transmission Oil is a bio-degradable universal hydraulic and transmission oil based on natural esters and selected additives.

- Natural high and stable viscosity index
- Very low pour point
- Good stability against oxidation
- Good extreme pressure and anti-wear properties
- Applicable in systems with "wet" brakes
- Excellent corrosion and foam preventing properties

Application:

This biodegradable universal tractor transmission oil (UTTO) has been developed for the hydraulics and transmissions of most generally used tractors and other agricultural equipment. This oil is especially suitable for situations where pollution of the environment can be expected and where the operating temperatures do not exceed 80 °C.

Performance Level:

API GL-4
Massey Ferguson
John Deere
Ford New Holland
Case
CEC L-33-T-82 > 90% (3 weeks)

Typical Characteristics:

Density at 15 °C, kg/l	0.903
Viscosity 40 °C, mm ² /s	46.50
Viscosity 100 °C, mm ² /s	10.00
Viscosity Index	211
Flash Point COC, °C	230
Pour Point, °C	-41
Total Base Number, mgKOH/g	4.7
Sulphate Ash, %	0.55

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

