

## Maxol Enercon F 5W/30

### Description:

Maxol Enercon F 5W/30 is a modern synthetic fuel economy motor oil produced with special selected synthetic base oils and a well-balanced choice of advanced additives.

- Lower fuel consumption
- High and stable viscosity index
- High resistance against shearing
- Fast cold start
- Very strong resistance against oxidation
- Safe lubrication film at high temperatures
- Very good detergency and dispersion power
- Very strong protection against wear, corrosion and foaming

### Application:

This fuel economy motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging. Suitable for passenger cars and vans with the specifications stated below. This motor oil is specially developed for cars requiring motor oils that fulfil the recent requirements of the OEM. This oil is fully backwards compatible with Ford M2C 913-A, B and C.

### Performance Level:

ACEA A1/B1, A5/B5
API SL/CF
Ford WSS-M2C913-D
Renault RN0700
VW VWC 53036

### Typical Characteristics:

Density at 15 °C, kg/l	0,850
Viscosity -30 °C, mPa.s	3890
Viscosity 40 °C, mm <sup>2</sup> /s	54,50
Viscosity 100 °C, mm <sup>2</sup> /s	9,90
Viscosity Index	170
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,1
Sulphate Ash, %	1,09

### Important:

Always observe the manufacturers specifications when selecting products.

Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

