

Maxol Multivis 15

Description:

Maxol Multivis 15 is a high-grade EP multigrade hydraulic oil based on carefully selected solvent refined base oils under addition of additives.

- High and stable viscosity index
- Excellent wear-preventing properties
- Very good activity against corrosion
- Excellent stability against oxidation
- Very good demulsification properties
- Very good deaerating and foam suppressing properties
- Good compatibility with seals and gaskets made from synthetic material
- Low pour point

Application:

This hydraulic fluid is of tailormade quality for heavy duty hydraulic systems of earthmoving equipment and of permanent installations that must work under high pressures over a wide temperature range. This fluid is not compatible in systems, containing parts or equipment with a silver lining.

Performance Level:

AFNOR NF E 48-603 HV
ASTM D 6158 HV
DIN 51524-3 HVLP
ISO 11158 HV

Typical Characteristics:

Density at 15°C, kg/l	0,888
Viscosity 40°, mm ² /s	15,60
Viscosity 100°C mm ² /s	3,83
Viscosity Index	143
Flash Point COC, °C	152
Pour Point, °C	-60
Total Base Number, mgKOH/g	0,40
Sulphate Ash, %	0,06

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

