

Maxol Tractor Trans Plus

Description:

A very high quality universal hydraulic and transmission oil formulated with high quality base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a high thermal stability
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

Application:

This very high quality universal tractor transmission oil (UTTO) has been developed for heavy loaded hydraulics and transmissions, with or without wet brakes, of agricultural and road-construction equipment. This oil can also be used in certain continuously variable transmissions (CVT) of agricultural and road-construction equipment.

Performance Level:

API GL-4
CNH MAT 3540/3525
Ford M2C86-C, M2C134-D
Massey Ferguson M1141/M1143/M1145
John Deere J20C/D
Allison C4, Cat TO-2, Case MS 1210
FNHA-2-C-200.00/201.00
Volvo WB 101
Valtra G2-08
ZF TE-ML 03E/05F/06K/17E/21F

Typical Characteristics:

Density at 15 °C, kg/l	0,885
Viscosity 40 °C, mm ² /s	60,00
Viscosity 100 °C, mm ² /s	9,30
Viscosity Index	136
Pour Point, °C	-45
Total Base Number, mgKOH/g	6,4

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

