

## Maxol Performance 10W/40

### Description:

Maxol Performance 10W/40 is a universal oil for cars and vans. It can be used in petrol and diesel engines, with or without turbo-charging.

- Lower fuel consumption
- Fast cold start
- Very good detergency and dispersion power
- Very strong protection against wear, corrosion and foaming

### Application:

This universal motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

### Performance Level:

ACEA A3/B4
API SL/CF
MB 229.1
VW 502.00/505.00

### Typical Characteristics:

Density at 15 °C, kg/l	0.869
Viscosity -25 °C, mPa.s	6170
Viscosity 40 °C, mm <sup>2</sup> /s	90.00
Viscosity 100 °C, mm <sup>2</sup> /s	13.50
Viscosity Index	152
Flash Point COC, °C	224
Pour Point, °C	-42
Total Base Number, mgKOH/g	10.2
Sulphate Ash, %	1.29

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

