

## Maxol Ultrafarm 10W/30

### Description:

Maxol Ultrafarm 10W/30 is an up-to-date multifunctional lubricating oil for agricultural and earthmoving equipment, formulated with top-grade, solvent-refined base oils and additives.

- Powerful dispersion and detergency
- High activity against wear, corrosion and foam
- Very strong resistance to oxidation
- Excellent extreme pressure properties
- High and stable viscosity index

### Application:

This multifunctional lubricant (known as a Super Tractor Oil Universal) has been developed to achieve one single lubricating oil that is able to lubricate:

- gasoline engines
- diesel engines (with or without turbo-charging)
- transmissions (also "wet" brakes)
- hydraulic systems

### Performance Level:

API SF/CG-4/GL-4
ACEA E3-96, Mil-L-2104D
Ford M2C159-C
Massey Ferguson M1139/M1144/M1145
John Deere J27/20C
Ford M2C134-D
Massey Ferguson M1135/M1143
ZF TE-ML 06B/07B
Allison C4
NH 410B
MB 227.1
Cat TO-2

### Typical Characteristics:

Density at 15 °C, kg/l	0.870
Viscosity -25 °C, mPa.s	5130
Viscosity 40 °C, mm <sup>2</sup> /s	68.00
Viscosity 100 °C, mm <sup>2</sup> /s	10.80
Viscosity Index	149
Flash Point COC, °C	220
Pour Point, °C	-36
Total Base Number, mgKOH/g	11.3
Sulphate Ash, %	1.55

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

