

Maxol Supersynth FE 0W/20

Description:

*A modern, synthetic, fuel economy motor oil based
On special selected synthetic base oils with a high
Viscosity index and a well-balanced choice of advanced
Additives to obtain the following properties:*

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion
and foaming

Performance Level:

ACEA C5, C6
API SQ Resource Conserving
ILSAC GF-7A
BMW Longlife-17 FE+
Jaguar Land Rover STJLR.03.5006
MB-Approval 229.71 / 229.72
Ford WSS-M2C954-A1 / WSS-M2C947-B1 / WSS-M2C962-A1
Opel OV 040 1547 - A20
Volvo VCC C6SP
VW VWC 53057
Chrysler MS-12145
Fiat 9.55535-GSX

Application:

*A modern fuel economy, special composed synthetic
motor oil suitable for use in petrol and diesel engines
of passenger cars and delivery vans. This oil is fully
backward compatible with BMW Longlife-14 FE+ and
Volvo VCC RBS0-2AE*

Typical Characteristics:

Density at 15°C, kg/l	0,847
Viscosity -35°C, mPa.s	5260
Viscosity 40°, mm ² /s	41,60
Viscosity 100°C mm ² /s	8,30
Viscosity Index	179
Flash Point COC, °C	222
Pour Point, °C	-51
Total Base Number, mgKOH/g	7,8
Sulphate Ash, %	0,77

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

