

Maxol Semi Synthetic 10W40

Description:

This motor oil is based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a good detergency and dispersion
- a safe lubrication film at high temperatures
- a strong protection against wear, corrosion and foaming.

Performance Level:

ACEA A3/B4
API SN/CF
MB 229.3
PSA B71 2300
Renault RN0700 / RN0710
VW 501.01 / 505.00

Application:

This all-round motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Typical Characteristics:

Density at 15°C, kg/l	0,866
Viscosity -25°C, mm ² /s	5690
Viscosity 40 °C, mm ² /s	100,00
Viscosity 100°C, mm ² /s	15,00
Viscosity Index	157
Flash Point COC, °C	238
Pour Point, °C	-42
Total Base Number, mgKOH/g	10,7
Sulphate Ash, %	1,32

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

