



SMOKE AND CARBON MONOXIDE ALARM PACK

PART CODE KCOSAC2

2030-DSR Smoke Alarm and
2030-DCR Carbon Monoxide Alarm
in a single pack



Overview

- Easy to set up and install
- Batteries Included
- 3-year manufacturer's warranty

Technical Specifications



2030-DSR Smoke Alarm



2030-DCR Carbon Monoxide (CO) Alarm

Sensor Type:	Optical	Electrochemical Sensor Technology
Primary Power Supply:	9V battery (supplied)	2 x AA alkaline batteries (supplied)
Sound Output Level:	85db (A) at 3 metres	85db (A) at 3 metres
Mounting Options:	Ceiling or wall-mounted	Wall-mounted or free-standing
Operating Temperature Range:	0°C to 40°C	-10°C to 45°C
Operating Humidity Range:	Up to 93% RH (non-condensing)	Up to 90% RH (non-condensing)
Storage and Transport:	-20°C to 60°C, 5% to 95% RH (non-condensing)	-20°C to 60°C, 5% to 95% RH (non-condensing)
Alarm Dimensions:	102mm x 36mm	96mm x 61mm x 38mm
Alarm Weight (including batteries):	118g	142g
Certification:	EN14604: 2005 (TUV)	EN50291-1: 2018 (TUV)
Warranty:	3-year warranty	3-year warranty



*Warranty excludes batteries